### (12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

## (19) World Intellectual Property Organization

International Bureau



## E COLOR CONTROL DE CONTROL CONT

(43) International Publication Date 3 February 2005 (03.02.2005)

**PCT** 

# (10) International Publication Number WO 2005/009879 A1

- (51) International Patent Classification7: B66B 1/16, 1/18
- (21) International Application Number:

PCT/US2003/019944

- (22) International Filing Date: 23 June 2003 (23,06,2003)
- (25) Filing Language:

English

(26) Publication Language:

English

- (71) Applicant (for all designated States except US): OTIS EL-EVATOR COMPANY [US/US]: 10 Farm Springs, Farmington, CT 06032 (US).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): VALK, MaryAnn [US/US]; 403 Founders Road, Glastonbury, CT 06033 (US). SIRAG, David [US/US]; 4 Rothe Lane, Ellington, CT 06029 (US).
- (74) Agent: OSBORN, Thomas: Otis Elevator Company. Intellectual Property Dept., 10 Farm Springs, Farmington, CT 06032 (US).

- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FL, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH. GM. KE. LS, MW. MZ. SD. SL. SZ. TZ. UG. ZM. ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ. DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

#### Declaration under Rule 4.17:


of inventorship (Rule 4.17(iv)) for US only

#### Published:

with international search report

[Continued on next page]

#### (54) Title: ELEVATOR DISPATCHING WITH BALANCED PASSENGER PERCEPTION OF WAITING



(57) Abstract: A perceived waiting time for a hall call to be answered by a car is determined as a constant times the square (46) of the summation (45) of remaining response time (39) and the amount of time that has expired since the call was registered (38). The time that may be perceived by a passenger to travel to the passenger's destination is determined as a constant times the square (51) of the distance between an estimated destination floor and the floor of the call and a constant times an estimated number of new hall stops and committed hall stops that each car will make (47). Perceived service time is (52) the sum of perceived wait time and perceived travel time. Constants are adjusted so that a long waiting time will yield a quick travel time. Assignment of calls to cars (60) is in accordance (61) with the smallest summation of square (59) of perceived service times for all waiting up calls and down calls.

#### 

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.